





浙江嘉善远东滚针轴承

YUANDONG PIN-BEARING FACTORY IN JIASHAN ZHEJIANG PROVINCE


R系列



开放型



双边防尘盖 (ZZ)



双边密封圈 (2NSL)

轴承型号 Bearing Number			外径 Bore	外径 O.D	宽度 Width	倒角(最小) Radius(min)	钢球 Lron shot		额定负荷(KN) Load Rating (KN)	
形式 Open	双面防尘盖 Double shield	双面密封圈 Double seal	d mm	D mm	开式/闭式 Open/closed	R mm	数量 Quantity	尺寸 Dimension	动 Move	静 Motionless
R2	R2ZZ	R2-2RS	3.175	9.525	3.969/3.969	0.15	8	1.3	0.5	0.19
R3	R3ZZ	R3-2RS	4.762	12.7	3.969/4.978	0.2	8	2.0	1.07	0.42
R4	R4	R4-2RS	6.350	15.875	4.978/4.978	0.2	8	2.381	1.47	0.60
R4A	R4A	R4A-2RS	6.350	19.05	5.556/7.144	0.2	6	3.969	2.80	1.06
R6	R6	R6-2RS	9.525	22.225	5.556/7.144	0.3	7	3.969	3.33	1.41
R8	R8	R8-2RS	12.70	28.575	6.35/7.9358	0.3	8	4.762	5.12	2.39
R10	R10	R10-2RS	15.875	34.925	7.144/8.73	0.3	10	4.762	6.00	3.27
R12	R12	R12-2RS	19.08	41.275	7.938/11.112	0.6	9	6.35	9.39	5.08
R14	R14	R14-2RS	22.225	47.625	9.525/12.7	0.6	10	6.35	10.07	5.81
R16	R16	R16-2RS	25.40	50.8	9.525/12.7	0.6	10	6.35	10.07	5.81