



62系列




浙江嘉善远东滚针轴承
YUANDONG PIN-BEARING FACTORY IN JIASHAN ZHEJIANG PROVINCE




开放式




单边防尘盖 (Z)



双边防尘盖 (ZZ)



单边密封圈 (NSL)



双边密封圈 (2NSL)

轴承型号 Bearing Number	孔径	外径	宽度	倒角	钢球 Iron shot		额定负荷(KN) Load Rating (KN)	
	Bore d mm inch	Outer diameter d mm inch	Width B mm inch	Radius R min mm inch	Size mm	Quantity N°	Dynamic Cr	Static Cor
625	5.1968	16.6299	5.1968	0.3.012	2.381	8	1.45	0.74
626	6.2362	19.7480	6.2362	0.3.0118	3.969	6	2.20	1.16
627	7.2756	22.8661	7.2756	0.3.0118	3.969	7	2.54	1.36
628	8.3149	24.9448	8.3149	0.3.0118	3.969	8	2.56	1.40
629	9.3543	26.10236	8.3149	0.3.0118	4.5	7	3.20	1.74
6200	10.3937	30.1.1811	9.3543	0.6.0236	4.763	8	3.94	2.23
6201	12.4724	32.1.2598	10.3973	0.6.0236	5.953	7	5.24	3.05
6202	15.5906	35.1.3780	11.4331	0.6.0236	5.953	8	5.85	3.49
6203	17.6693	40.1.5748	12.4724	0.6.0236	6.747	8	7.37	4.48
6204	20.7874	47.1.8504	14.5512	1.0.0394	7.938	8	9.88	6.20
6205	25.9843	52.2.0470	15.5906	1.1.0433	7.938	9	10.78	6.98
6206	30.1.1811	62.2.4409	16.6299	1.5.0591	9.525	9	14.90	10
6207	35.1.3780	72.2.8346	17.6693	2.0787	11.112	9	19.74	15.92
6208	40.1.5748	80.3.1496	18.7087	2.0787	12.0	9	22.70	17.70
6209	45.1.7717	85.3.3465	19.7480	2.0787	12.0	10	24.35	19.82
6210	50.1.9685	90.3.5433	20.7874	2.0787	12.7	10	26.97	25.09