






69系列




开放型




单边防尘盖 (Z)



双边防尘盖 (ZZ)



单边密封圈 (NSL)



双边密封圈 (2NSL)

轴承 型号 Bearing Number	孔径	外径	宽度	倒角	钢球 Iron shot		额定负荷(KN) Load Rating (KN)	
	Bore d mm inch	Outer diameter d mm inch	Width B mm inch	Radius R min mm inch	Size mm	Quantity N°	Dynamic Cr	Static Cor
696	6.2362	15.5906	5.1968	0.15.060	2.381	8	1.13	0.56
697	7.2756	17.6693	5.1968	0.3.012	2.381	9	1.23	0.63
698	8.3150	19.7480	6.2362	0.3.012	3.175	7	1.73	0.87
699	9.3543	20.7874	6.2362	0.3.012	3.175	8	3.81	3.15
61900	10.3937	22.8661	6.2362	0.3.012	3.175	9	2.07	1.12
61901	12.4724	24.9449	6.2362	0.3.012	3.175	10	2.22	1.24
61902	15.5906	28.1.024	7.2756	0.3.012	3.969	10	3.32	1.94
61903	17.6693	30.1.1811	7.2756	0.3.012	3.969	11	3.51	2.13
61904	20.7874	37.1.4567	9.3543	0.3.012	4.763	11	4.91	3.07
61905	25.9843	42.1.6535	9.3543	0.3.012	4.763	12	5.12	3.35
61906	30.1.1811	47.1.8504	9.3543	0.3.012	4.763	14	5.54	3.91
61907	35.1.3780	55.2.1654	10.3937	0.6.024	5.953	13	7.75	5.63
61908	40.1.5748	62.2.4409	12.4724	0.6.024	6.747	13	9.98	7.28
61909	45.1.7716	68.2.6772	12.4724	0.6.024	6.747	15	10.87	8.40
61910	50.1.9685	72.2.8347	12.4724	0.6.024	6.747	15	10.68	8.40
61911	55.2.1654	80.3.1496	13.5118	0.624	6.747	17	11.40	9.52
61912	60.2.3622	85.3.3464	13.5118	1.040	6.747	18	11.58	10.08
61913	65.2.559	90.3.543	13.5118	1.040	7.938	17	11.40	9.52
61914	70.2.756	100.3.937	16.630	1.040	9.525	15	15.51	13.95
61915	75.2.953	105.4.134	16.630	1.040	9.525	16	16.01	14.73
61916	80.3.150	110.4.331	16.630	1.040	9.525	17	16.20	15.50