




浙江嘉善远东滚针轴承


YUANDONG PIN-BEARING FACTORY IN JIASHAN ZHEJIANG PROVINCE

无带内圈针轴承 密封型

SEALED NEEDLE ROLLER BEARINGS WITHOUT INNER RINGS
RNA49...RS, RNA49...2RS



RNA49...RS



RNA49...2RS

轴径 Shaft Diameter	轴承型号 Bearing Designation		外型尺寸 Boundary Dimensions				基本额定负荷 Basic Load Ratings		极限转速 Limiting Speed
	RNA49...RS 单面密封	RNA49...2RS 双面密封	Fw	D	C	Rs	动 C	静 CO	油润滑 Oil
	Mm	Single sealed	double sealed	Mm		Min	N		Rpm
14	RNA4900RS	RNA4900.2RS	14	22	13	0.3	6800	6900	13000
16	RNA4901RS	RNA4901.2RS	16	24	13	0.3	7600	8300	12000
20	RNA4902RS	RNA1902.2RS	20	28	13	0.3	8600	10300	10000
22	RNA4903RS	RNA4903.2RS	22	30	13	0.3	8800	11000	9000
25	RNA4904RS	RNA4904.2RS	25	37	17	0.3	17300	19900	7500
30	RNA4905RS	RNA4905.2RS	30	42	17	0.3	19300	24200	6500
35	RNA4906RS	RNA4906.2RS	35	47	17	0.3	21100	28500	5500
42	RNA4907RS	RNA4907.2RS	42	55	20	0.6	26500	39500	4800
46	RNA4908RS	RNA4908.2RS	48	62	22	0.6	36000	53000	42000
52	RNA4909RS	RNA4909.2RS	52	68	22	0.6	38000	59000	3900
58	RNA4940RS	RNA4940.2RS	58	72	22	0.6	40000	64000	3500

Tn=塑料保险架，允许运转温度：120℃连续地，150℃临时地，180℃短时地。')对于脂润滑，允许值为表列数值的60%。·有档圈，无润滑油孔和槽，如需要油孔和槽时，需在轴承代号上增加ASR1。


TN: plastic retainer, permissible operational temperature 120℃, 150℃ for temporary use, 180℃ for short time only') for grease lub, the permissible value should be 60% of those in the list 'with retaining ring, no lubricating holes or grooves, please add ASR1 before the bearing code if oil holes or grooves are needed for your products.

无带内圈针轴承 密封型


SEALED NEEDLE ROLLER BEARINGS WITHOUT INNER RINGS
RNA49...RS, RNA49...2RS



浙江嘉善远东滚针轴承
YUANDONG PIN-BEARING FACTORY IN JIASHAN ZHEJIANG PROVINCE



RNA49...RS



RNA49...2RS

轴径 Shaft Diameter	轴承型号 Bearing Designation		外型尺寸 Boundary Dimensions						基本额定负荷 Basic Load Ratings		极限转速 Limiting Speed
	RNA49..RS 单面密封 Single sealed	RNA49..2RS 双面密封 double sealed	D	F	D	C	B	Rs	动 C	静 CO	油润滑 Qil
Mm			Mm					Min	N		Rpm
14	RNA4900RS	RNA4900.2RS	10	14	22	13	14	0.3	6800	6900	13000
16	RNA4901RS	RNA4901.2RS	12	16	24	13	14	0.3	7600	8300	12000
20	RNA4902RS	RNA1902.2RS	15	20	28	13	14	0.3	8600	10300	10000
22	RNA4903RS	RNA4903.2RS	17	22	30	13	14	0.3	8800	11000	9000
25	RNA4904RS	RNA4904.2RS	20	25	37	17	18	0.3	17300	19900	7500
30	RNA4905RS	RNA4905.2RS	25	30	42	17	18	0.3	19300	24200	6500
35	RNA4906RS	RNA4906.2RS	30	35	47	17	18	0.3	21100	28500	5500
42	RNA4907RS	RNA4907.2RS	35	42	55	20	21	0.6	26500	39500	4800
46	RNA4908RS	RNA4908.2RS	40	48	62	22	23	0.6	36000	53000	42000
52	RNA4909RS	RNA4909.2RS	45	52	68	22	23	0.6	38000	59000	3900
58	RNA4940RS	RNA4940.2RS	50	58	72	22	23	0.6	40000	64000	3500

Tn=塑料保险架，允许运转温度：120℃连续地，150℃临时地，180℃短时地。')对于脂润滑，允许值为表列数值的60%。·有档圈，无润滑油孔和槽，如需要油孔和槽时，需在轴承代号上增加ASR1。
TN: plastic retainer, permissible operational temperature 120℃, 150℃ for temporary use, 180℃ for short time only') for grease lub, the permissible value should be 60% of those in the list ·with retaining ring, no lubricating holes or grooves, please add ASR1 before the bearing code if oil holes or grooves are needed for your products.